



US standard



GROWING TOGETHER

XL GRIP (ADT)



PRODUCT DATA SHEET



Bias



XL GRIP (ADT)



XL GRIP (ADT) is a bias-ply tire for Articulated dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

Performance



Cut and Chip Resistance



Durability



Hard Rocky Surface



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 25"	94057863	26.5 - 25	TL	28	-	STD	E-3	-	68.5	26.8	31.3	202.8	46	816	22.00/3.0	-
	94057870	26.5 - 25	TL	32	-	STD	E-3	-	68.5	26.8	31.3	202.8	46	849	22.00/3.0	-
	94057887	29.5 - 25	TL	28	-	STD	E-3	-	73.2	29.9	33.4	218.3	49	985	25.00/3.5	-
	94057894	29.5 - 25	TL	32	-	STD	E-3	-	73.2	29.9	33.4	218.3	49	1023	25.00/3.5	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference