

AS 504

TIRE SIZE	24X8.50 - 12
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	81 A8
LI/SS FREE ROLLING	94 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	216	RIM REC	7 JA; 7.00 I
OD (MM)	610	ECE	E11-106R-0010452
SLR (MM)	284	PR	6
RC (MM)	1761		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.30
10 FR	940
25 FR	795
30 FR	750
40 FR	670
10 DW	645
25 DW	550
30 DW	515
40 DW	462

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.