


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>650/55 R 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	STREUMASCHINE / TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94038855	<b>RC (IN)</b>	167.6
<b>SW (IN)</b>	25.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	54.7	<b>ECE</b>	E4-106R-000806
<b>SLR (IN)</b>	24.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3730	4310	4890	5940	6880	7930	8970	9670	10710	11640
40	4100	4740	5380	6530	7550	8700	9850	10610	11770	12790
30	4960	5730	6500	7900	9140	10530	11930	12850	14240	15480
25	5570	6440	7310	8870	10270	11840	13400	14440	16000	17390
15	6470	7480	8490	10310	11930	13750	15560	16780	18590	20200
5	7370	8520	9670	11870	13580	15650	17720	19110	21170	23010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.