

MINE STAR



MINE STAR

MINE STAR is a bias-ply tyre which is an excellent choice for heavy-duty underground mining operations. It features high cut/chip and puncture resistance providing improved operational efficiency. MINE STAR is made of a special compound and features a special tread design resulting in an extended tyre life-cycle.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø15"	38X16 -15	TT	-	32		11.5	-	0		990	0	0	28,5	STD
	35X15 -15	TT	-	32	-	11.0	11.50 11.00 BD	0		885	0	0	23,5	STD
	8.25 - 15	TT	-	20	-	6.5	6.0 7.0	0		848	0	0	19	STD
	35X15 -15	TT	-	20	-	11.0	11.50 11.00 BD	0		885	0	0	23,5	STD

STD: STANDARD

TECHNOLOGIES			PERFORMANCES			
						
						

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION	
					REC RIM	ALT RIM								
														
35X15 -15	TL	-	32	-	11.0	11.50 11.00 BD	0		885	0	0	23,5	STD	
32X14.50/15 -15	TT	-	28		11.0	11.50 11.00 BD 10.50	0		825	0	0	23,5	STD	
38X16 -15	TL	-	32		11.5	-	0		990	0	0	28,5	STD	
Ø25"	55X19.00 -25	TL	L5	50	-	14.00	-	0		1400	632	4280	69	STD
	55X19.00 -34	TL	L5	50	-	16.00	-	0		1435			64	STD

STD: STANDARD



TECHNOLOGIES					PERFORMANCES			
								
	L5							
								
-	-							

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026