


AGRIMAX V- FLECTO

TIRE SIZE	VF 480/80 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	166 D



DIMENSIONS US STANDARD

CODE USA	94067220	RC (IN)	203.5
SW (IN)	18.9	RIM REC	DW 16 L
OD (IN)	68.2	RIM ALT	DW 15 L
SLR (IN)	30.5	ECE	E11-106R-007168

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5000	5740	6590	7440	8290	9150	10000	10630
FROM 40 TO 25	5500	6320	7250	8180	9120	10050	10990	11680
20	5610	6440	7400	8340	9300	10250	11210	11920
12	5710	6570	7540	8510	9480	10450	11420	12150
5	6050	6940	7970	9010	10030	11060	12090	12850
*UPTO 5 CYC WITH FRONT LOADER	7690	8840	10150	11450	12760	14080	15380	16360
5 HT	5610	6440	7400	8340	9300	10250	11210	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.