

FL 635

TIRE SIZE	710/40 R 22.5
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	BALER / HARVESTER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	161 D



DIMENSIONS IS STANDARD

SW (MM)	727	RIM REC	AG 24.00
OD (MM)	1140	ECE	E11-106R-003014
SLR (MM)	510	SRI	550
RC (MM)	3467		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1350	1540	1730	2150	2445	2825	3200	3495	3835	4210
65	1480	1690	1900	2360	2685	3100	3515	3840	4210	4625
50	1795	2050	2300	2860	3250	3755	4260	4650	5100	5600
40	2015	2300	2580	3210	3650	4215	4785	5225	5725	6290
30	2240	2555	2865	3565	4055	4680	5310	5800	6360	6985
25	2340	2670	3000	3730	4240	4900	5560	6070	6655	7310
10	2665	3040	3415	4250	4830	5580	6330	6910	7580	8325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.