

AGRIMAX RT 765

TIRE SIZE	580/70 R 38
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	180 D



DIMENSIONER US STANDARD

USA CODE	94075133	RC (IN)	216.7
SW (IN)	22.7	RIM REC	W 18 L
OD (IN)	71.9	RIM ALT	DW 18 L; DD 18 L
SLR (IN)	32.3	ECE	E11-106R-005836

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58	64	67
40	7010	8540	10870	12080	13230	14260	15280	16250	17170	17640
30	7360	8970	11420	12690	13890	14980	16050	17060	18030	18520
25	7680	9360	11900	13240	14480	15620	16730	17800	18820	19310
20	8070	9830	12500	13900	15210	16410	17570	18690	19750	20280
15	8310	10130	12890	14320	15670	16910	18110	19260	20360	20900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.