


# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>270/95 R 44</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94028146	<b>RC (IN)</b>	196.2
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	64.3	<b>RIM ALT</b>	W 8 ; W 10
<b>SLR (IN)</b>	30.1	<b>ECE</b>	E4-106R-00784

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	2280	2990	3630	3980	4210	4620	5030	5430	5830	-
25	2280	2990	3630	3980	4210	4620	5030	5430	5830	-
20	2450	3200	3890	4270	4510	4950	5390	5830	6260	-
5	2720	3430	4210	5000	5790	5960	6670	7360	8070	8760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.