


AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 10.0/75 - 15.3 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 106 A8 |
| LI/SS FREE ROLLING | 119 A8 |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 264 | RIM REC | 9.00 |
| OD (MM) | 785 | ECE | E11-106R-003509 |
| SLR (MM) | 360 | PR | 8 |
| RC (MM) | 2404 | SRI | 360 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.10 |
|------------|------|
| 10 FR | 1905 |
| 25 FR | 1620 |
| 30 FR | 1525 |
| 40 FR | 1360 |
| 10 DW | 1330 |
| 25 DW | 1130 |
| 30 DW | 1065 |
| 40 DW | 950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.