


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>620/75 R 30 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / COTTON PICKER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	168 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	625	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1692	<b>ECE</b>	E4-106R-001420
<b>SLR (MM)</b>	779	<b>SRI</b>	800
<b>RC (MM)</b>	5169		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	2580	2970	3640	3980	4370	4760	5155	5600
40	2580	2970	3640	3980	4370	4760	5155	5600
30	2760	3180	3900	4260	4680	5100	5520	5995
15 CYC	4255	4900	6010	6565	7210	7855	8505	9240
10 CYC	4640	5345	6555	7160	7865	8570	9275	10080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.