


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>480/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN FÖR FRUKTODLING / LITEN TRAKTOR / TRAKTOR / SKÖRDEMASKIN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	149 A8 ; 149 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94075232	<b>RC (IN)</b>	188.4
<b>SW (IN)</b>	19.3	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	62.2	<b>RIM ALT</b>	W 14 L; W 16 L
<b>SLR (IN)</b>	28.5	<b>ECE</b>	E11-106R-009042

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	3380	3870	4450	5020	5590	6170	6740	7170
25	3380	3870	4450	5020	5590	6170	6740	7170
20	3620	4150	4770	5380	5990	6610	7220	7680
5 LT	4520	5200	5970	6730	7500	8270	9030	9610
5 HT	3620	4150	4770	5380	5990	6610	7220	7680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.