

FLOTATION 648

TIRE SIZE	700/50 - 26.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	PRESSE À PAILLE / MOISSONNEUSE / ÉPANDÉUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	162 A8/158 B
LI/SS FREE ROLLING	174 A8/170 B



DIMENSIONS US STANDARD

CODE USA	94006526	RC (IN)	161.4
SW (IN)	27.6	RIM REC	24.00
OD (IN)	54.1	ECE	E4-106R-002279
SLR (IN)	24.4	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	32	35
5 FR	18580	19640	20680
10 FR	16720	17680	18610
20 FR	14860	15720	16540
25 FR	13270	14030	14770
30 FR	11950	12630	13230
5 DW	13180	13930	14660
10 DW	11860	12540	13190
20 DW	10540	11140	11730
25 DW	9410	9950	10470
30 DW	8480	8960	9370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.