

## AGRIMAX FORCE

|                  |                                                          |
|------------------|----------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 710/60 R 34 CFO</b>                                |
| <b>UM</b>        | US STANDARD                                              |
| <b>MACHINERY</b> | MOISSONNEUSE / TRACTEUR DE<br>FORTE PUISSANCE / TRACTEUR |
| <b>VERSION</b>   | SPECIAL                                                  |
| <b>TIRE TYPE</b> | TL                                                       |
| <b>LI/SS</b>     | 170 D                                                    |



### DIMENSIONS US STANDARD

|                 |          |                 |                |
|-----------------|----------|-----------------|----------------|
| <b>CODE USA</b> | 94060061 | <b>RC (IN)</b>  | 201.8          |
| <b>SW (IN)</b>  | 27.9     | <b>RIM REC</b>  | DW 25 B        |
| <b>OD (IN)</b>  | 67.6     | <b>ECE</b>      | E4-106R-001485 |
| <b>SLR (IN)</b> | 30.0     | <b>TRA CODE</b> | R1W            |

### LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| <b>45</b>            | 5530  | 6370  | 7340  | 8180  | 9140  | 9990  | 11190 | 12040 |
| <b>FROM 40 TO 25</b> | 6080  | 7010  | 8070  | 8990  | 10050 | 10980 | 12300 | 13200 |
| <b>20</b>            | 6330  | 7290  | 8390  | 9350  | 10450 | 11410 | 12790 | 13760 |
| <b>12</b>            | 6570  | 7560  | 8710  | 9710  | 10850 | 11850 | 13280 | 14290 |
| <b>5</b>             | 7730  | 8900  | 10240 | 11420 | 12760 | 13930 | 15620 | 16800 |
| <b>UPTO 20 CYC</b>   | 7900  | 9100  | 10480 | 11680 | 13060 | 14260 | 15980 | 17200 |
| <b>UPTO 10 CYC</b>   | 9420  | 10860 | 12500 | 13930 | 15570 | 17010 | 19060 | 20500 |
| <b>UPTO 5 CYC</b>    | 10340 | 11920 | 13710 | 15290 | 17080 | 18660 | 20910 | 22490 |
| <b>5 HT</b>          | 6330  | 7290  | 8390  | 9350  | 10450 | 11410 | 12790 | 13760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.