


AGRIMAX RT 657

TIRE SIZE	480/65 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	140 D ; 143 A8



DIMENSIUNI US STANDARD

USA CODE	94062621	RC (IN)	146.9
SW (IN)	18.9	RIM REC	W 15 L
OD (IN)	48.6	RIM ALT	W 14 L
SLR (IN)	22.1	ECE	E4-106R-000617

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2650	3090	3470	3860	4240	4570	5070	5510
30	2780	3240	3650	4060	4460	4810	5320	5790
25	2890	3370	3790	4210	4630	4990	5530	6010
20	3040	3550	4000	4440	4880	5270	5830	6340
5 LT	3550	4140	4660	5170	5690	6140	6800	7390
5 HT	3040	3550	4000	4440	4880	5270	5830	6340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.