

# AGRIMAX RT 855

|                  |                                                                                 |
|------------------|---------------------------------------------------------------------------------|
| <b>TIRE SIZE</b> | <b>320/85 R 24</b>                                                              |
| <b>UM</b>        | IS STANDARD                                                                     |
| <b>MACHINERY</b> | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| <b>VERSIÓN</b>   | STANDARD                                                                        |
| <b>TIRE TYPE</b> | TL                                                                              |
| <b>LI/SS</b>     | 122 A8/B                                                                        |

## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 329  | <b>RIM REC</b> | W 11           |
| <b>OD (MM)</b>  | 1154 | <b>RIM ALT</b> | W 9 ; W 10     |
| <b>SLR (MM)</b> | 519  | <b>ECE</b>     | E4-106R-000613 |
| <b>RC (MM)</b>  | 3424 | <b>SRI</b>     | 550            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 825  | 960  | 1095 | 1230 | 1365 | 1500 |
| <b>40</b>    | 825  | 960  | 1095 | 1230 | 1365 | 1500 |
| <b>30</b>    | 885  | 1030 | 1175 | 1320 | 1465 | 1605 |
| <b>10 LT</b> | 1110 | 1290 | 1470 | 1650 | 1830 | 2010 |
| <b>10 HT</b> | 885  | 1030 | 1175 | 1320 | 1465 | 1605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

