


# FLOTATION 648

<b>TIRE SIZE</b>	<b>750/60 - 30.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	164 A8/160 B
<b>LI/SS FREE ROLLING</b>	176 A8/172 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	754	<b>RIM REC</b>	AG 24.00
<b>OD (MM)</b>	1675	<b>ECE</b>	E11-106R-003410
<b>SLR (MM)</b>	710	<b>PR</b>	12
<b>RC (MM)</b>	4935		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.60	1.70
10 FR	9240	9595	9940
20 FR	8315	8635	8945
30 FR	7390	7680	7950
40 FR	6600	6855	7100
50 FR	5940	6170	6300
10 DW	6505	6755	7000
20 DW	5855	6080	6300
30 DW	5200	5405	5600
40 DW	4645	4825	5000
50 DW	4180	4345	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.