

# LG 306

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | <b>20X10.00 - 10</b>                  |
| <b>UM</b>           | US STANDARD                           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                |
| <b>MACHINERY</b>    | FAUCHEUSE / MICRO TRACTEUR / TRACTEUR |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TL                                    |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94012459 | <b>RC (IN)</b> | 58.0            |
| <b>SW (IN)</b>  | 9.8      | <b>RIM REC</b> | 8.00 I - 55     |
| <b>OD (IN)</b>  | 20.0     | <b>RIM ALT</b> | 7.00 I - 55     |
| <b>SLR (IN)</b> | 8.9      | <b>ECE</b>     | E11-106R-003455 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 10               | 1455      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.