

# TF 9090

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 7.50 - 20                       |
| <b>UM</b>           | US STANDARD                     |
| <b>CONSTRUCTION</b> | BIAS                            |
| <b>MACHINERY</b>    | TRACTOR MIC / TRACTOR / REMORCĂ |
| <b>VERSION</b>      | SPECIAL                         |
| <b>TIRE TYPE</b>    | TT                              |
| <b>LI/SS</b>        | 105 A8                          |



## DIMENSIUNI US STANDARD

|                 |          |                |        |
|-----------------|----------|----------------|--------|
| <b>USA CODE</b> | 94038817 | <b>RC (IN)</b> | 107.3  |
| <b>SW (IN)</b>  | 8.1      | <b>RIM REC</b> | 5.50 F |
| <b>OD (IN)</b>  | 36.0     | <b>RIM ALT</b> | 5.00 F |
| <b>SLR (IN)</b> | 17.0     | <b>PR</b>      | 8      |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>56</b> |
| 25               | 2040      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.