

EARTHMAX SR 33



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 33



EARTHMAX SR 33 is a radial tire for multipurpose trucks. Its multi-block tread pattern has been specially designed to guarantee extraordinary traction on soft, sandy, or muddy surfaces. The strong All Steel casing features excellent durability and resistance to snag and punctures.



SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION	
				REC RIM	ALT RIM						
											
Ø20"	335/80 R 20	TL	-	150 K	11	-	335	1047	464	3145	STD
	395/85 R 20	TL	-	168 J	10.00W	10.00HF	394	1184	538	3589	STD
	14.00 R 20	TL	-	164/160 J	10.0	10.00W 9.0	390	1250	576	3840	STD
	365/80 R 20 (14.5 R 20)	TL	-	152 K	11	-	360	1096	496	3318	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES	
			
			
K	168 kg		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index