


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 540/65 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 152 D ; 155 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 530 | RIM REC | W 16 L |
| OD (MM) | 1566 | RIM ALT | W 18 L |
| SLR (MM) | 712 | ECE | E4-106R-000652 |
| RC (MM) | 4742 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|--------------|------|------|------|------|------|------|------|------|
| 65 | 1705 | 1990 | 2240 | 2485 | 2735 | 2950 | 3270 | 3550 |
| 50 | 1795 | 2090 | 2350 | 2615 | 2875 | 3100 | 3435 | 3730 |
| 40 | 1860 | 2170 | 2445 | 2715 | 2985 | 3220 | 3565 | 3875 |
| 30 | 1965 | 2290 | 2575 | 2860 | 3150 | 3395 | 3760 | 4085 |
| 10 LT | 2285 | 2670 | 3000 | 3335 | 3670 | 3955 | 4380 | 4760 |
| 10 HT | 1965 | 2290 | 2575 | 2860 | 3150 | 3395 | 3760 | 4085 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.