


AGRIMAX SPARGO SB

| | |
|---------------------|--|
| TIRE SIZE | VF 380/90 R 54 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / PULVERIZATOR |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 176 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|---------------------------|
| SW (MM) | 395 | RIM REC | W13 |
| OD (MM) | 2060 | RIM ALT | W12;DW12;W13A; DW13;DW13A |
| SLR (MM) | 957 | ECE | E11-106R-0010178 |
| RC (MM) | 6310 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1 | 1.2 | 1.4 | 1.6 | 1.8 | 2 | 2.2 | 2.4 | 2.6 | 2.8 | 3 | 3.2 | 3.4 | 3.6 | 3.8 | 4 | 4.2 | 4.4 |
|----------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|
| 70 | 2780 | 3105 | 3495 | 3815 | 4010 | 4205 | 4335 | 4465 | 4690 | 4915 | 5110 | 5305 | 5465 | 5625 | 5790 | 5950 | 6210 | 6465 |
| FROM 65 TO 40 | 3055 | 3410 | 3835 | 4190 | 4405 | 4615 | 4760 | 4900 | 5150 | 5400 | 5610 | 5825 | 6000 | 6180 | 6355 | 6535 | 6820 | 7100 |
| 30 | 3120 | 3480 | 3915 | 4275 | 4495 | 4710 | 4855 | 5000 | 5255 | 5510 | 5725 | 5945 | 6125 | 6305 | 6485 | 6670 | 6960 | 7245 |
| 20 | 3180 | 3545 | 3990 | 4360 | 4580 | 4805 | 4950 | 5100 | 5355 | 5615 | 5835 | 6060 | 6245 | 6425 | 6610 | 6795 | 7090 | 7385 |
| 10 | 3360 | 3750 | 4220 | 4610 | 4845 | 5080 | 5235 | 5390 | 5665 | 5940 | 6170 | 6405 | 6600 | 6795 | 6990 | 7190 | 7500 | 7810 |
| UPTO 30 CYC | 3470 | 3870 | 4355 | 4760 | 5000 | 5240 | 5405 | 5565 | 5845 | 6130 | 6370 | 6610 | 6815 | 7015 | 7215 | 7420 | 7740 | 8060 |
| UPTO 15 CYC | 4140 | 4620 | 5200 | 5680 | 5970 | 6260 | 6450 | 6645 | 6980 | 7315 | 7605 | 7895 | 8135 | 8375 | 8615 | 8855 | 9240 | 9625 |
| UPTO 10 CYC | 4535 | 5065 | 5695 | 6225 | 6540 | 6855 | 7070 | 7280 | 7650 | 8015 | 8335 | 8650 | 8915 | 9175 | 9440 | 9705 | 10125 | 10545 |
| 10 HT | 3120 | 3480 | 3915 | 4275 | 4495 | 4710 | 4855 | 5000 | 5255 | 5510 | 5725 | 5945 | 6125 | 6305 | 6485 | 6670 | 6960 | 7245 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.