


AGRIMAX V-FLECTO



TIRE SIZE	VF 710/60 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	171 D

ABMESSUNGEN IS STANDARD

SW (MM)	708	RIM REC	DW 25 B
OD (MM)	1820	RIM ALT	DW 23 B
SLR (MM)	794	ECE	E11-106R-004520
RC (MM)	5447	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	3075	3580	4080	4585	5090	5595
FROM 65 TO 40	3380	3935	4485	5040	5595	6150
30	3445	4010	4570	5140	5705	6270
20	3515	4090	4660	5240	5815	6395
10	3715	4325	4930	5540	6150	6765
*UPTO 10 CYC WITH FRONT LOADER	4730	5505	6275	7055	7830	8610
10HT	3445	4010	4570	5140	5705	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.