


AGRIMAX RT 600

800/65 R 32

| | |
|---------------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |

181 A8 ; 178 B



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94039302 | RC (IN) | 218.8 |
| SW (IN) | 30.5 | RIM REC | DW 27 B |
| OD (IN) | 71.7 | RIM ALT | DH 27 B; DW 25 B |
| SLR (IN) | 32.4 | ECE | E4-106R-001429 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 64 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 7000 | 8070 | 9890 | 10800 | 11870 | 12930 | 14000 | 15210 | 16530 | - | - |
| 25 | 7610 | 8760 | 10750 | 11740 | 12900 | 14050 | 15210 | 16530 | 18190 | - | - |
| 20 | 8150 | 9380 | 11510 | 12570 | 13800 | 15050 | 16280 | 17690 | 19470 | - | - |
| 5 LT | 10200 | 11750 | 14410 | 15740 | 17280 | 18840 | 20390 | 22160 | 24370 | - | - |
| 5 HT | 8150 | 9380 | 11510 | 12570 | 13800 | 15050 | 16280 | 17690 | 19470 | - | - |
| 5 CYC | - | 12470 | 15940 | 17550 | 20390 | 22350 | 24370 | 26510 | 27420 | 28660 | 30860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.