


# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>340/85 R 28</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL           |
| <b>MACHINERY</b>    | FELDSPRITZE /<br>TRAUBENERNTEMASCHINE /<br>TRACTOR / ERNTEMASCHINE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 127 A8/B   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA-CODE</b> | 94021611 | <b>RC (IN)</b> | 153.1          |
| <b>SW (IN)</b>  | 13.9     | <b>RIM REC</b> | W 12           |
| <b>OD (IN)</b>  | 50.7     | <b>RIM ALT</b> | W 11           |
| <b>SLR (IN)</b> | 23.1     | <b>ECE</b>     | E4-106R-000593 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 30        | 2130 | 2470 | 2820 | 3160 | 3520 | 3860 |
| 25        | 2130 | 2470 | 2820 | 3160 | 3520 | 3860 |
| 20        | 2280 | 2650 | 3020 | 3390 | 3770 | 4130 |
| 5 LT      | 2840 | 3320 | 3780 | 4240 | 4710 | 5170 |
| 5 HT      | 2280 | 2650 | 3020 | 3390 | 3770 | 4130 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.