

## AW 705

|                           |                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>          | <b>15.0/55 - 17</b>                                                                          |
| <b>UM</b>                 | US STANDARD                                                                                  |
| <b>CONSTRUCTION</b>       |  BIAS       |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE |
| <b>VERSION</b>            | STANDARD                                                                                     |
| <b>TIRE TYPE</b>          | TL                                                                                           |
| <b>LI/SS FREE ROLLING</b> | 155 A8                                                                                       |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94054022 | <b>RC (IN)</b> | 102.5           |
| <b>SW (IN)</b>  | 15.0     | <b>RIM REC</b> | 13.00           |
| <b>OD (IN)</b>  | 33.5     | <b>RIM ALT</b> | 13; W 13        |
| <b>SLR (IN)</b> | 15.0     | <b>ECE</b>     | E11-106R-004251 |

### LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>103</b> |
|------------------|------------|
| <b>5 FR</b>      | 11960      |
| <b>15 FR</b>     | 10160      |
| <b>20 FR</b>     | 9570       |
| <b>25 FR</b>     | 8540       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.