


# AS 504

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	106 A8
<b>LI/SS FREE ROLLING</b>	119 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	264	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	785	<b>ECE</b>	E11-106R-003509
<b>SLR (MM)</b>	360	<b>PR</b>	8
<b>RC (MM)</b>	2404	<b>SRI</b>	360

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.10</b>
10 FR	1905
25 FR	1620
30 FR	1525
40 FR	1360
10 DW	1330
25 DW	1130
30 DW	1065
40 DW	950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.