


FL 630 ULTRA

| | |
|---------------------|--|
| TIRE SIZE | 600/50 R 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | STREUMASCHINE / TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 159 D ; 170 A8 |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1172 | ECE | E11-106R-003960 |
| SLR (MM) | 518 | SRI | 550 |
| RC (MM) | 3533 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70 | 1280 | 1480 | 1675 | 2020 | 2355 | 2680 | 3020 | 3330 | 3670 | 3985 |
| 65 | 1400 | 1620 | 1840 | 2220 | 2585 | 2950 | 3310 | 3660 | 4025 | 4375 |
| 50 | 1695 | 1960 | 2225 | 2700 | 3125 | 3575 | 4000 | 4420 | 4875 | 5295 |
| 40 | 1920 | 2220 | 2520 | 3040 | 3540 | 4050 | 4555 | 5020 | 5520 | 6000 |
| 25 | 2215 | 2560 | 2905 | 3510 | 4080 | 4675 | 5210 | 5800 | 6365 | 6915 |
| 10 | 2520 | 2915 | 3310 | 4000 | 4650 | 5325 | 5940 | 6600 | 7245 | 7875 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.