

# AW 702

<b>TIRE SIZE</b>	<b>6.00 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	95 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94009879	<b>RC (IN)</b>	86.5
<b>SW (IN)</b>	6.7	<b>RIM REC</b>	4.00 E
<b>OD (IN)</b>	28.4	<b>RIM ALT</b>	4.50 E; 4½ K
<b>SLR (IN)</b>	13.1	<b>ECE</b>	E4-106R-001958

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>40</b>
5 FR	2130
15 FR	1810
20 FR	1710
25 FR	1520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.