

# AGRIMAX FORCE

|                  |                                                   |
|------------------|---------------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 710/55 R 28 CFO</b>                         |
| <b>UM</b>        | IS STANDARD                                       |
| <b>MACHINERY</b> | ERNTemaschine /<br>HOCHLEISTUNGSTRAKTOR / TRACTOR |
| <b>VERSION</b>   | STANDARD                                          |
| <b>TIRE TYPE</b> | TL                                                |
| <b>LI/SS</b>     | 165 D                                             |

## ABMESSUNGEN IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 716  | <b>RIM REC</b>  | DW 25 B         |
| <b>OD (MM)</b>  | 1493 | <b>ECE</b>      | E11-106R-005498 |
| <b>SLR (MM)</b> | 663  | <b>SRI</b>      | 700             |
| <b>RC (MM)</b>  | 4442 | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR           | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|----------------------|------|------|------|------|------|------|------|------|
| <b>70</b>            | 2150 | 2475 | 2855 | 3185 | 3555 | 3885 | 4350 | 4685 |
| <b>FROM 65 TO 40</b> | 2365 | 2725 | 3140 | 3500 | 3910 | 4270 | 4785 | 5150 |
| <b>30</b>            | 2455 | 2830 | 3265 | 3640 | 4065 | 4440 | 4975 | 5355 |
| <b>20</b>            | 2550 | 3940 | 3390 | 3780 | 4220 | 4610 | 5165 | 5560 |
| <b>10</b>            | 3000 | 3460 | 3985 | 4445 | 4965 | 5420 | 6075 | 6540 |
| <b>UPTO 30 CYC</b>   | 3070 | 3540 | 4080 | 4550 | 5080 | 5550 | 6220 | 6695 |
| <b>UPTO 15 CYC</b>   | 3665 | 4220 | 4865 | 5425 | 6060 | 6615 | 7415 | 7980 |
| <b>UPTO 10 CYC</b>   | 4020 | 4630 | 5335 | 5950 | 6645 | 7255 | 8130 | 8755 |
| <b>10 HT</b>         | 2455 | 2830 | 3265 | 3640 | 4065 | 4440 | 4975 | 5355 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

