

# TR 678

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>780/50 - 28.5</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | IMPLEMENT MACHINERY / TRAILER /<br>IMPLEMENTS / FORESTRY /<br>EXCAVATOR / TRAILER |
| <b>VERSION</b>      | STEEL BELTED  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 190 A2 ; 182 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 770  | <b>RIM REC</b>  | AG 26.00        |
| <b>OD (MM)</b>  | 1515 | <b>ECE</b>      | E11-106R-006975 |
| <b>SLR (MM)</b> | 701  | <b>PR</b>       | 24              |
| <b>RC (MM)</b>  | 4642 | <b>TRA CODE</b> | LS2             |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>6.00</b> |
| 40                | 8500        |
| 10                | 10600       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.