


# AS 504

<b>TIRE SIZE</b>	<b>7.50 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	92 A8
<b>LI/SS FREE ROLLING</b>	104 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94019304	<b>RC (IN)</b>	97.4
<b>SW (IN)</b>	8.2	<b>RIM REC</b>	5.50 F
<b>OD (IN)</b>	31.6	<b>RIM ALT</b>	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
<b>SLR (IN)</b>	14.6	<b>PR</b>	6

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33
5 FR	2780
15 FR	2360
20 FR	2230
25 FR	1980
5 DW	1940
15 DW	1650
20 DW	1550
25 DW	1390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.