

FLOTATION 648

| | |
|---------------------|---|
| | 600/50 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALYA MAKINESİ / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKİNE |
| VERSION | DUAL BEAD |
| TIRE TYPE | TL |
| | 156 A8/152 B |
| | 169 A8/165 B |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1170 | ECE | E11-106R-004392 |
| SLR (MM) | 510 | PR | 20 |
| RC (MM) | 3501 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.00 | 3.10 | 3.20 |
|------------|------|------|------|
| 10 FR | 7820 | 7975 | 8120 |
| 20 FR | 7035 | 7175 | 7310 |
| 30 FR | 6255 | 6380 | 6495 |
| 40 FR | 5585 | 5695 | 5800 |
| 50 FR | 5025 | 5125 | 5150 |
| 10 DW | 5390 | 5495 | 5600 |
| 20 DW | 4850 | 4945 | 5040 |
| 30 DW | 4310 | 4395 | 4480 |
| 40 DW | 3850 | 3925 | 4000 |
| 50 DW | 3465 | 3535 | 3550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.