



US standard



GROWING TOGETHER

# V-FLEXA



PRODUCT DATA SHEET



Radial



191



# V-FLEXA

V-FLEXA is a radial tire specifically designed for agricultural trailers. It is a latest-generation flotation product featuring VF technology, which enables the transport of heavy loads both in the fields and on the road with an inflation pressure that is 30% less than that of a standard tire of the same size. Additional steel belts confer major resistance to the casing against impacts. Not only does V-FLEXA support heavy loads in full safety, it also avoids soil compaction thanks to perfect weight distribution. Moreover, V-FLEXA features great self-cleaning properties, durability as well as low rolling resistance.

**Technologies**



VF Technology



High Speed



Reinforced Bead



Extra Steel Belted

**Performance**



Reduced Soil Compaction



Traction



High Load Capacity



Durability



Low Rolling Resistance

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 22.5"	9406629	VF 560/60 R 22.5	166 D	AG 16.00	-	21.9	49.2	21.7	147.9	31	323	SB
Ø 26.5"	94063949	VF 600/55 R 26.5	167 D	AG 20.00	-	24.2	52.8	22.8	156.9	31	354	SB
	94066056	VF 600/65 R 26.5	172 D	AG 20.00	-	24.2	57.2	24.7	172.3	31	417	SB
	94065103	VF 650/55 R 26.5	171 D	AG 20.00	-	25.4	54.7	23.3	161.4	31	394	SB
	94074839	VF 710/50 R 26.5	176 D	AG 24.00	-	28.6	54.4	23.6	165.1	31	423	SB
	94074822	VF 750/45 R 26.5	176 D	AG 24.00	-	29.7	53.1	23.0	161.2	32	434	SB
	94512751	VF 800/45 R 26.5	179 D	AG 28.00	AG 24.00	31.7	54.8	23.7	165.9	33	467	SB
Ø 30.5"	94074846	VF 710/50 R 30.5	178 D	AG 24.00	-	28.6	58.5	25.7	177.6	31	470	SB
	94073139	VF 750/60 R 30.5	187 D	AG 24.00	-	30.7	66.1	28.7	200.2	33	625	SB
	94073139	VF 750/60 R 30.5	187 D	AG 24.00	-	30.7	66.1	28.7	200.2	33	625	SB
Ø 32"	94076611	VF 800/60 R 32 (VF 30.5 L R 32) <b>NEWSIZE</b>	191 D	DW 27 B	DW 25 B	32.2	70.8	30.9	214.9	35	661	SB

SB: Steel Belted

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference