



PRINTED ON  
23-04-2026

DATA SHEET

# BK-LOADER 53

<b>TIRE SIZE</b>	<b>405/70 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	LOADER
<b>VERSION</b>	ARAMID BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155A2/151A4



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94054428	<b>RC (IN)</b>	131.5
<b>SW (IN)</b>	16.0	<b>RIM REC</b>	13
<b>OD (IN)</b>	43.2	<b>RIM ALT</b>	14; 13 SDC; 12;12 SDC
<b>SLR (IN)</b>	20.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	36	44	51	58	65	73	80
12	2670	3350	3980	4610	5240	5820	6400	6990	7610
5	3030	3800	4520	5240	5950	6610	7270	7940	8540
STATIC	4850	6060	7220	8380	9530	10580	11680	12680	13670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.