


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 600/70 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	165 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94060047	<b>RC (IN)</b>	189.0
<b>SW (IN)</b>	23.7	<b>RIM REC</b>	DW 21 B; DW 21 A
<b>OD (IN)</b>	63.1	<b>RIM ALT</b>	DW 20 A; DW 20 B
<b>SLR (IN)</b>	27.9	<b>ECE</b>	E11-106R-006495

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	4850	5570	6390	7230	8050	8870	9700	10330
<b>FROM 40 TO 25</b>	5330	6130	7030	7950	8850	9750	10670	11400
20	5540	6370	7310	8260	9200	10140	11090	11810
12	5750	6610	7590	8580	9560	10530	11520	12260
5	6770	7780	8930	10090	11230	12380	13550	14420
<b>UPTO 20 CYC</b>	6930	7960	9140	10330	11500	12680	13870	14760
<b>UPTO 10 CYC</b>	8270	9490	10890	12310	13710	15110	16530	17590
<b>UPTO 5 CYC</b>	9060	10420	11950	13500	15050	16580	18130	19300
5 HT	5540	6370	7310	8260	9200	10140	11090	11810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.