


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>460/85 R 34</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	475	<b>RIM REC</b>	W 16 L
<b>OD (MM)</b>	1646	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (MM)</b>	721	<b>ECE</b>	E11-106R-006759
<b>RC (MM)</b>	4865	<b>SRI</b>	775

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>50</b>	1660	1955	2255	2510	2805	3060	3360	3615	3955	4250
<b>40</b>	1660	1955	2255	2510	2805	3060	3360	3615	3955	4250
<b>30</b>	1755	2095	2415	2685	3005	3280	3595	3870	4235	4550
<b>10 LT</b>	2225	2620	3020	3365	3760	4105	4500	4845	5300	5695
<b>10 HT</b>	1900	2245	2585	2875	3215	3510	3850	4140	4530	4870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.