


AW 711

TIRE SIZE	340/60 R 16.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STUBBLE RESISTANT
TIRE TYPE	TL
LI/SS	145 A8/B



ABMESSUNGEN IS STANDARD

SW (MM)	324	RIM REC	11
OD (MM)	820	ECE	E4-106R-001392
SLR (MM)	368	SRI	390
RC (MM)	2476		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
50	870	1135	1395	1595	1860	2120	2265	2495	2730	2900
40	870	1135	1395	1595	1860	2120	2265	2495	2730	2900
30	975	1270	1560	1790	2080	2375	2535	2795	3055	3250
25	1040	1350	1660	1905	2215	2525	2695	2975	3250	3455
20	1100	1430	1755	2015	2340	2670	2855	3145	3440	3655
10	1220	1585	1950	2235	2600	2965	3170	3495	3820	4060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.