

PL 801

| | |
|---------------------|--|
| TIRE SIZE | 5.00 - 8 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | RASTRILLO HILERADOR ROTATIVO / COSECHADORA / CARRETILLA ELEVADORA / COSECHADORA / MAQUINARIA AGRÍCOLA / CARRETILLA ELEVADORA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TT |



DIMENSIONES IS STANDARD

| | | | |
|----------------|--------|------------|-----------------|
| SW (MM) | 135 | ECE | E11-106R-003381 |
| OD (MM) | 468 | PR | 8 |
| RIM REC | 3.00 D | | |
| RIM ALT | 3.25 I | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 8.30 |
|--------------------|------|
| 25 LOAD WHEEL | 1235 |
| 25 STEER WHEEL | 950 |
| 10 OTHER VEHICLES | 1235 |
| 25 OTHER VEHICLES | 950 |
| STATIC SIDE LOADER | 1435 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.