


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>440/80 R 34 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 A8 ; 155 D



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94038657	<b>RC (IN)</b>	188.0
<b>SW (IN)</b>	17.4	<b>RIM REC</b>	DW 14 L
<b>OD (IN)</b>	61.7	<b>RIM ALT</b>	DW 15 L; DW 16 L
<b>SLR (IN)</b>	27.7	<b>ECE</b>	E4-106R-002295

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	4010	4960	5810	6750	7610	8540
30	4270	5270	6170	7180	8080	9080
25	4530	5600	6560	7620	8590	9640
20	4730	5830	6830	7940	8950	10050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.