


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 520/85 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 173 A8/B |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------------------------|
| CODICE USA | 94040544 | RC (IN) | 248.4 |
| SW (IN) | 20.3 | RIM REC | DW 16 L ; W 16 A ; W 16 L ; DD 16 |
| OD (IN) | 81.7 | RIM ALT | DW 18 L ; W 18 L ; W 18 A |
| SLR (IN) | 38.0 | ECE | E4-106R-001494 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 5160 | 6000 | 6840 | 7680 | 8530 | 9370 | 10750 | 11750 | 12750 | 13610 | 14330 |
| 25 | 5160 | 6000 | 6840 | 7680 | 8530 | 9370 | 10750 | 11750 | 12750 | 13610 | 14330 |
| 20 | 5520 | 6430 | 7330 | 8230 | 9140 | 10030 | 11500 | 12580 | 13650 | 14560 | 15330 |
| 5 LT | 6910 | 8040 | 9170 | 10300 | 11430 | 12550 | 14410 | 15740 | 17080 | 18240 | 19200 |
| 5 HT | 5520 | 6430 | 7330 | 8230 | 9140 | 10030 | 11500 | 12580 | 13650 | 14560 | 15330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.