


AGRIMAX RT 855

TIRE SIZE	420/80 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	151 D ; 162 A2



ABMESSUNGEN US STANDARD

USA-CODE	94046089	RC (IN)	222.1
SW (IN)	16.5	RIM REC	W 13
OD (IN)	72.4	RIM ALT	W 12
SLR (IN)	34.0	ECE	E4-106R-001730

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	3580	4110	4720	5320	5940	6550	7080	7610
30	3760	4320	4960	5600	6240	6880	7440	7990
25	3920	4510	5170	5840	6500	7180	7760	8330
20	4120	4730	5430	6130	6830	7530	8150	8750
5	4930	5650	6490	7330	8170	9010	9740	10470
5 LT	4790	5510	6330	7140	7960	8770	9490	10200
5 HT	4120	4730	5430	6130	6830	7530	8150	8750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.