


AGRIMAX FORCE

| | |
|---------------------|--|
| TIRE SIZE | IF 710/55 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 165 D |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|-----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 25 B |
| OD (MM) | 1493 | ECE | E11-106R-005498 |
| SLR (MM) | 663 | SRI | 700 |
| RC (MM) | 4442 | TRA CODE | R1W |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|----------------------|------|------|------|------|------|------|------|------|
| 70 | 2150 | 2475 | 2855 | 3185 | 3555 | 3885 | 4350 | 4685 |
| FROM 65 TO 40 | 2365 | 2725 | 3140 | 3500 | 3910 | 4270 | 4785 | 5150 |
| 30 | 2455 | 2830 | 3265 | 3640 | 4065 | 4440 | 4975 | 5355 |
| 20 | 2550 | 3940 | 3390 | 3780 | 4220 | 4610 | 5165 | 5560 |
| 10 | 3000 | 3460 | 3985 | 4445 | 4965 | 5420 | 6075 | 6540 |
| UPTO 30 CYC | 3070 | 3540 | 4080 | 4550 | 5080 | 5550 | 6220 | 6695 |
| UPTO 15 CYC | 3665 | 4220 | 4865 | 5425 | 6060 | 6615 | 7415 | 7980 |
| UPTO 10 CYC | 4020 | 4630 | 5335 | 5950 | 6645 | 7255 | 8130 | 8755 |
| 10 HT | 2455 | 2830 | 3265 | 3640 | 4065 | 4440 | 4975 | 5355 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.