

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 500/50 - 17 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 137 A8/133 B |
| LI/SS FREE ROLLING | 149 A8/145 B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 510 | RIM REC | 16.00 |
| OD (MM) | 945 | ECE | E4-106R-001885 |
| SLR (MM) | 416 | PR | 14 |
| RC (MM) | 2750 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.20 | 2.40 | 2.80 |
|------------|------|------|------|
| 10 FR | 3950 | 4160 | 4550 |
| 20 FR | 3555 | 3740 | 4095 |
| 30 FR | 3160 | 3325 | 3640 |
| 40 FR | 2820 | 2970 | 3250 |
| 50 FR | 2540 | 2675 | 2900 |
| 10 DW | 2795 | 2940 | 3220 |
| 20 DW | 2515 | 2645 | 2900 |
| 30 DW | 2235 | 2350 | 2575 |
| 40 DW | 1995 | 2100 | 2300 |
| 50 DW | 1795 | 1890 | 2060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.