

# AT 111

|                     |                     |
|---------------------|---------------------|
| <b>TIRE SIZE</b>    | <b>AT 18X10 - 8</b> |
| <b>UM</b>           | US STANDARD         |
| <b>CONSTRUCTION</b> | ⊠ BIAS              |
| <b>MACHINERY</b>    | VEHÍCULO ATV        |
| <b>VERSIÓN</b>      | STANDARD            |
| <b>TIRE TYPE</b>    | TL                  |



## DIMENSIONES US STANDARD

|                   |          |                |                |
|-------------------|----------|----------------|----------------|
| <b>CÓDIGO USA</b> | 94026845 | <b>RIM ALT</b> | 7.5 AT; 8.5 AT |
| <b>SW (IN)</b>    | 10.0     | <b>ECE</b>     | E4-75R-0006322 |
| <b>OD (IN)</b>    | 18.0     | <b>PR</b>      | 4              |
| <b>RIM REC</b>    | 8.0 AT   |                |                |

## LOAD CAPACITY (LBS/TIRE)

|                  |          |
|------------------|----------|
| <b>MPH / PSI</b> | <b>5</b> |
| 62               | 225      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.