

RIDEMAX FL 693 M



TIRE SIZE	560/60 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	161 D ; 158 E

РАЗМЕРЫ IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1244	RIM ALT	16.00 ; 17.00 ; AG 20.00
SLR (MM)	549	ECE	E4-106R-000630
RC (MM)	3767	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1555	1745	2170	2465	2850	3230	3530	3870	4250
65	1690	1900	2360	2685	3100	3515	3840	4210	4625
50	2050	2300	2860	3250	3755	4260	4650	5100	5600
40	2300	2580	3210	3650	4215	4785	5225	5725	6290
25	2670	3000	3730	4240	4900	5560	6070	6655	7310
10	3040	3415	4250	4830	5580	6330	6910	7580	8325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.