


AGRIMAX RT 855

TIRE SIZE	520/85 R 46
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	158 A8/B



DIMENSIONER US STANDARD

USA CODE	94062072	RC (IN)	242.4
SW (IN)	20.3	RIM REC	DW 16 L ; W 16 A ; W 16 L ; DD 16
OD (IN)	80.8	RIM ALT	DW 18 L ; W 18 L ; W 18 A
SLR (IN)	36.6	ECE	E4-106R-001415

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	5160	6000	6840	7680	8530	9370
25	5160	6000	6840	7680	8530	9370
20	5520	6430	7330	8230	9140	10030
5 LT	6910	8040	9170	10300	11430	12550
5 HT	5520	6430	7330	8230	9140	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.