


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	425/55 R 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	129 D ; 140 A8

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94059324	<b>RC (IN)</b>	106.5
<b>SW (IN)</b>	16.5	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	35.2	<b>ECE</b>	E11-106R-005104
<b>SLR (IN)</b>	15.6		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58
40	1310	1680	2080	2370	2730	3110	3390	3710	4080
30	1590	2030	2520	2870	3320	3760	4100	4500	4940
25	1760	2260	2810	3200	3690	4190	4570	5020	5510
20	1970	2540	3150	3580	4130	4680	5110	5610	6160
15	2070	2650	3300	3750	4320	4910	5360	5870	6450
5	2360	3020	3750	4270	4930	5590	6100	6690	7340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.