


AGRIMAX FORCE

TIRE SIZE	IF 710/60 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	SPECIAL
TIRE TYPE	TL
LI/SS	170 D



DIMENSIONI US STANDARD

CODICE USA	94060061	RC (IN)	201.8
SW (IN)	27.9	RIM REC	DW 25 B
OD (IN)	67.6	ECE	E4-106R-001485
SLR (IN)	30.0	TRA CODE	R1W

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5530	6370	7340	8180	9140	9990	11190	12040
FROM 40 TO 25	6080	7010	8070	8990	10050	10980	12300	13200
20	6330	7290	8390	9350	10450	11410	12790	13760
12	6570	7560	8710	9710	10850	11850	13280	14290
5	7730	8900	10240	11420	12760	13930	15620	16800
UPTO 20 CYC	7900	9100	10480	11680	13060	14260	15980	17200
UPTO 10 CYC	9420	10860	12500	13930	15570	17010	19060	20500
UPTO 5 CYC	10340	11920	13710	15290	17080	18660	20910	22490
5 HT	6330	7290	8390	9350	10450	11410	12790	13760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.