


# AGRIMAX FORCE



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>IF 750/75 R 46</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SKÖRDEMASKIN / MOTORSTARK<br>TRAKTOR / TRAKTOR   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 186 D  |

## DIMENSIONER US STANDARD

|                 |          |                 |                 |
|-----------------|----------|-----------------|-----------------|
| <b>USA CODE</b> | 94058082 | <b>RC (IN)</b>  | 267.8           |
| <b>SW (IN)</b>  | 29.2     | <b>RIM REC</b>  | DW 25 B         |
| <b>OD (IN)</b>  | 90.3     | <b>ECE</b>      | E11-106R-006491 |
| <b>SLR (IN)</b> | 40.6     | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45                   | 8950  | 10280 | 11810 | 13340 | 14860 | 16380 | 17910 | 19060 |
| <b>FROM 40 TO 25</b> | 9840  | 11310 | 12980 | 14660 | 16340 | 18010 | 19690 | 20900 |
| 20                   | 10230 | 11760 | 13500 | 15240 | 16990 | 18730 | 20470 | 21780 |
| 12                   | 10630 | 12210 | 14020 | 15830 | 17640 | 19440 | 21250 | 22620 |
| 5                    | 12500 | 14360 | 16490 | 18620 | 20740 | 22870 | 25000 | 26600 |
| <b>UPTO 20 CYC</b>   | 12790 | 14690 | 16880 | 19060 | 21230 | 23410 | 25580 | 27230 |
| <b>UPTO 10 CYC</b>   | 15260 | 17530 | 20120 | 22720 | 25320 | 27910 | 30510 | 32460 |
| <b>UPTO 5 CYC</b>    | 16730 | 19220 | 22070 | 24920 | 27770 | 30610 | 33460 | 35600 |
| 5HT                  | 10230 | 11760 | 13500 | 15240 | 16990 | 18730 | 20470 | 21780 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.