


RIDEMAX IT 697 (M+S)

| | |
|---------------------|--|
| TIRE SIZE | 540/65 R 28 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D ; 160 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 530 | RIM REC | W 16 L |
| OD (MM) | 1413 | RIM ALT | W 18 |
| SLR (MM) | 642 | ECE | E11-106R-004076 |
| RC (MM) | 4276 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 1820 | 2250 | 2635 | 3060 | 3450 | 3875 |
| 50 | 1965 | 2425 | 2845 | 3305 | 3725 | 4185 |
| 40 | 2115 | 2610 | 3060 | 3555 | 4005 | 4500 |
| 30 | 2185 | 2695 | 3160 | 3675 | 4140 | 4650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.